



SCHREIBER
SINCE 1815



**MARQUEES
MANUFACTURER**

Floors

Floor in fir boards for party tents

Construction

- Galvanised steel grid construction: rectangular bars 4x1.6" (100x40 mm) around and 1.6x1.6" (40x40 mm) on the length and width.
- The floor is attached to the structure.
- Panels of fir planed on 4 sides.

Presentation

- Boards are glued and screwed on rafters each 37.5" (95 cm) to get panels of 10x3.25' (60x40 mm)
- Rafters in fir: 4x1.6"
- Resistance of the floor: 500 kg/sqm
- Weight: +/- 18 kg/sqm.

Floor in fir boards for aluminium structures

Construction

- Galvanised steel grid construction: rectangular bars 4x1.6" (100x40 mm) around and 2.35x1.6" (60x40 mm) on the length and 1.6x1.6" (40x40 mm) on the width.
- Aluminium profile 5.5x2.5" (140x65 mm) to make junction each 16.5' (5 m) in the width of the boards. Finishing aluminium sheet on the two external lengths.
- Panels of fir boards (thickness 4.7x0.8" (120x20 mm) planed on 4 sides.

Presentation

- 7 boards of 16.5' (5 m) length glued and screwed on rafters each 40" (100 cm) in order to get panels of 16.5' x 23.5" (60x500 cm).
- Rafters in fir: 2.4x1.6"
- Resistance of the floor: 500 kg/sqm
- Weight: +/- 18 kg/sqm.

Multiplex floor for aluminium structures

Construction

- Galvanised steel grid construction: rectangular bars 2.4x2.4" (60x60 mm) around the base of the structure and around each element of 8.2x3.25' (2,50x1 m) One rectangular bar 1.6x1.6" (40x40 mm) in the middle of each element to rigidify the floor.

Multiplex floor elements are composed of

- Anti-slip multiplex panels, thickness 0.7" (18 mm) dimensions: 8.2x3.25' on which are screwed 2 aluminium profiles 3.75x3.25" (95x60 mm) (n°1) and one aluminium profile 2.35x1.6" (60x40 mm) in the middle (n° 2). The profiles n° 1 are fitted into each other (saving time by setting up).

- Resistance of the floor: 500 kg/sqm.
- Weight: +/- 24 kg/sqm.

